



SAFETY DATA SHEET

EA081-1

HI BUILD EPOXY LINING ACTIVATOR

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

EA081-1
HI BUILD EPOXY LINING ACTIVATOR

RECOMMENDED USE

Industrial epoxy coating designed for steel used in heavy-duty maintenance, oil field and OEM applications. Can also be used as a tank lining depending on the content of the tank.

MANUFACTURER

TCI Coatings, Inc.
4501 Bradley St
Lubbock, TX 79415
U.S.A.
Telephone: 1-800-880-8244

EMERGENCY TELEPHONE NUMBER

1-800-424-9300 (Chemtrec)

2. HAZARDS IDENTIFICATION

This product is a mixture and has been classified based on the current information available for the individual ingredients, in accordance with OSHA regulation 29CFR1910.1200(d)(3).

HAZARD CLASSIFICATION

- Acute Toxicity, Inhalation - Category 4
- Skin Corrosion/Irritation - Category 1
- Serious Eye Damage/Irritation - Category 1
- Respiratory or Skin Sensitization - Category 1B (skin); Respiratory - Category 1
- Germ Cell Mutagenicity - Category 2
- Carcinogenicity - Category 1**
- Reproductive Toxicity - Category 2
- Specific Target Organ Toxicity, Single Exposure - Category 1 (lungs by inhalation)**
- Specific Target Organ Toxicity, Repeated Exposure - Category 1 (lungs)**, Category 2 (kidney, liver, skin, CNS)
- Flammable Liquid - Category 2

PICTOGRAM



SIGNAL WORD

DANGER!

HAZARD STATEMENT

Highly flammable liquid and vapor. Harmful if inhaled. Causes severe skin burns and serious eye damage. May cause an allergic skin reaction and may cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing genetic defects and of damaging fertility or the unborn child. May cause cancer. May cause damage to the kidneys, liver, skin and central nervous system through repeated or prolonged exposure and causes damage to the lungs** by inhalation.

****This product may contain crystalline silica. (Please see Section 3 for the specific composition of this product.)**
Long-term exposure to high levels of silica dust may cause lung damage (silicosis) and cancer. This can only occur when sanding or abrading the dry film.

PRECAUTIONARY STATEMENT

PREVENTION: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe fumes or vapors. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation, wear respiratory protection. Keep away from heat, sparks, open flames, hot surfaces, pilot lights and all other sources of ignition-No smoking. Keep cool and tightly closed. Ground/bond container and receiving equipment. Use explosion-proof ventilating and lighting equipment. Use only non-sparking tools. Take pre-cautionary measures against static discharge. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, face and eye protection. Do not eat, drink or smoke when using this product.

RESPONSE: In case of fire: Use dry chemical or Carbon Dioxide (CO2). Do not use water. If exposed, concerned, feel unwell or if experiencing respiratory symptoms: Seek medical attention. If Swallowed: Do NOT induce vomiting. Rinse mouth and immediately call a poison center. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you continue to feel unwell. If on skin (or hair): Take off immediately all contaminated clothing and wash it before reuse. Wash skin with plenty of soap and water. If skin irritation occurs: Get medical attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses. Continue rinsing. If eye irritation persists, seek medical attention.

STORAGE: Store locked up in a well-ventilated place. Keep cool.

DISPOSAL: Dispose of contents in accordance with local, state and national regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#	% BY WEIGHT	CHEMICAL NAME
14807-96-6	21 - 30	TALC (HYDROUS MAGNESIUM SILICATE)
100-51-6	11 - 20	BENZYL ALCOHOL
14808-60-7	1 - 10	CRYSTALLINE QUARTZ
1330-20-7	1 - 10	MIXED XYLENES
110839-13-9	1 - 10	4,4-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC
2855-13-2	1 - 10	ISOPHORONE DIAMINE
25620-58-0	1 - 10	TRIMETHYLHEXAMETHYLENEDIAMINE
108-95-2	1 - 10	PHENOL
2807-30-9	1 - 10	ETHYLENE GLYCOL MONOPROPYL ETHER
1477-55-0	1 - 10	METAXYLENEDIAMINE
112-57-2	1 - 10	TETRAETHYLENEPENTAMINE
69-72-7	< 1	SALICYLIC ACID
100-41-4	< 1	ETHYL BENZENE

4. FIRST AID MEASURES

NECESSARY MEASURES

INHALATION: Move to fresh air. If not breathing or breathing is difficult: Give artificial respiration or oxygen by trained personnel. Get medical attention immediately.

EYE CONTACT: Check for and remove any contact lenses. Immediately flush with large amounts of water for at least 15 minutes. In case of eye irritation: Get medical attention.

SKIN CONTACT: Wash affected areas with soap and water or a recognized skin cleaner. Do NOT use solvents or thinners. Remove contaminated clothing and shoes. In case of skin irritation: Get medical attention.

INGESTION: Get medical attention immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious or convulsing person.

POTENTIAL HEALTH EFFECTS AND SYMPTOMS

INHALATION: Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause damage to the respiratory system and lungs. Symptoms may include chest pain, shortness of breath, coughing, retching, and coughing up mucus or blood.

EYE CONTACT: Causes serious eye damage. This may be experienced as itching, pain, stinging, swelling, impaired vision or blindness.

SKIN CONTACT: Causes severe skin burns. Symptoms may include a burning sensation, bleeding, bloody scabs, ulcers, blanching of the skin, blisters and black or dead skin.
May cause an allergic skin reaction.

INGESTION: Ingestion can result in irritation and possible corrosive action in the mouth, stomach tissue and digestive tract. Symptoms may include vomiting, nausea, diarrhea, pain, and bleeding.

INDICATION OF MEDICAL ATTENTION AND SPECIAL TREATMENT

If irritation or any symptoms of overexposure occur during or after use of this product, contact a POISON CONTROL CENTER at 1-800-222-1222 or an EMERGENCY ROOM or PHYSICIAN immediately. Have Safety Data Sheet information available.

5. FIRE FIGHTING MEASURES

FLAMMABILITY OF PRODUCT

Flashpoint: 55°F

Lower Explosive Limit: 0.1%

Upper Explosive Limit: 15.8

EMERGENCY RESPONSE GUIDEBOOK (ERG)

Use Guide 128.

EXTINGUISHING MEDIA

Use dry chemical, carbon dioxide (CO₂), or foam. (If product contains alcohol, use alcohol-resistant foam). Water may not be suitable as an extinguishing media, but helpful in keeping adjacent containers cool.

SPECIFIC HAZARDS

HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water. Substance may be transported hot.

Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation. Runoff from fire control or dilution water may cause pollution.

PROTECTIVE EQUIPMENT FOR FIREFIGHTERS

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode. Structural firefighters' protective clothing will only provide limited protection.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate.

PROTECTIVE EQUIPMENT

Use only non-sparking equipment to handle spilled material and absorbent. Put on appropriate personal protective

equipment (see Section 8).

EMERGENCY PROCEDURES

Call Chemtrec at 1-800-424-9300 for emergency response. Isolate spill or leak area immediately. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering.

MATERIALS FOR CONTAINMENT AND CLEANING UP

Inert absorbent material, e.g. sand, earth, vermiculite or diatomaceous earth.

METHODS FOR CONTAINMENT AND CLEANING UP

Approach release from upwind. Stop leak if you can do so without risk. Contain spill or leak by creating a dike and cover with absorbent material. Shovel or sweep into an appropriate waste disposal container. Prevent entry into waterways, sewers, basements or confined areas.

7. HANDLING AND STORAGE

HANDLING

Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation, wear respiratory protection. Do not breathe fumes or vapors. Use appropriate clothes and personal protective equipment (see section 8). Contaminated work clothing should not be allowed out of the workplace. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Do not take internally. Keep out of reach of children.

This product is flammable. Keep away from heat, sparks, open flames, or any other ignition source. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Ground/bond container and receiving equipment.

STORAGE

Store in accordance with local regulations. Store in original container protected from direct sunlight and moisture in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Do not store above 100°F.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES

CHEMICAL NAME	EXPOSURE LIMITS
TALC (HYDROUS MAGNESIUM SILICATE)	OSHA PEL TWA: 20 mppc1 ACGIH TLV TWA: 2 mg/m3 (respirable dust)
BENZYL ALCOHOL	WEEL TWA ; 10 ppm
CRYSTALLINE QUARTZ	OSHA PEL & ACGIH TLV: 0.1 mg/m3 (respirable dust)
MIXED XYLENES	ACGIH & OSHA-TWA: 100 ppm; ACGIH & OSHA-STEL: 150 ppm
4,4-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC	NONE ESTABLISHED
ISOPHORONE DIAMINE	NONE ESTABLISHED
TRIMETHYLHEXAMETHYLENEDIAMINE	NONE ESTABLISHED
PHENOL	ACGIH TWA: 5 ppm; OSHA PEL: 5 ppm
ETHYLENE GLYCOL MONOPROPYL ETHER	NONE ESTABLISHED
METAXYLENEDIAMINE	

TETRAETHYLENEPENTAMINE	NONE ESTABLISHED
SALICYLIC ACID	WEEL TWA: 5 mg/m#
ETHYL BENZENE	NONE ESTABLISHED
	OSHA & ACGIH TWA: 100 ppm / OSHA & ACGIH STEL: 125 ppm

ENGINEERING CONTROLS

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

INDIVIDUAL PROTECTION MEASURES

RESPIRATORY PROTECTION

If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator approved by NIOSH/MSHA. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

SKIN AND BODY PROTECTION

Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Protective gloves, apron, boots, head and face protection may be required to prevent contact. Gloves should be chemical-resistant and impervious and comply with an approved standard.

When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

EYE PROTECTION

To prevent eye contact, wear safety glasses, chemical goggles, and/or head and face protection, depending on the task being performed and the risks involved.

OTHER MEASURES

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	UPPER EXPLOSIVE LIMIT
Liquid.	15.8
ODOR	LOWER EXPLOSIVE LIMIT
Amine like.	0.1%
ODOR THRESHOLD	VAPOR PRESSURE
Not determined.	Not determined.
PH	VAPOR DENSITY
Not applicable.	Heavier than air.
FREEZING POINT	RELATIVE DENSITY (g/cm³)
below 0°F	1.28
INITIAL BOILING POINT	SOLUBILITY IN WATER
277°F	Insoluble.
FLASH POINT	PARTITION COEFFICIENT: N-OCTANOL/WATER
55°F	Not determined.
EVAPORATION RATE	AUTO-IGNITION TEMPERATURE

Slower than ether.	Not determined.
FLAMMABILITY (SOLID, GAS)	DECOMPOSITION TEMPERATURE
Not applicable	Not determined.
V.O.C.	VISCOSITY
1.176 lb/gl	No data available.

10. STABILITY AND REACTIVITY

REACTIVITY

No specific test data related to reactivity available for this product or its ingredients.

CHEMICAL STABILITY

This product is stable.

POSSIBILITY OF HAZARDOUS REACTIONS

Under normal conditions of storage and use, hazardous reactions will not occur.

CONDITIONS TO AVOID

Avoid all possible sources of ignition (spark, heat or flame). Isolate from any incompatible materials.

INCOMPATIBLE MATERIALS

Strong oxidizers such as permanganates, chromates and peroxides. Strong acids and bases.

HAZARDOUS DECOMPOSITION PRODUCTS

In case of fire, fumes may contain carbon oxides, metal oxides, nitrogen oxides, or other unidentified organic compounds.

11. TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF EXPOSURE

Inhalation, ingestion and skin absorption.

SYMPTOMS

See section 4.

MEASURES OF ACUTE TOXICITY

Toxicological testing has not been conducted for this product as a whole. Available toxicological data for individual ingredients is summarized below:

ETHYL BENZENE (100-41-4):

- LD50 Oral: 3,500 mg/kg (rat)
- LD50 Dermal: 15,433 mg/kg (rabbit)
- LC50 Inhalation: 35,500 mg/m³, 2h (mouse)

BENZYL ALCOHOL (100-51-6):

- LD50 Oral: 1,040 mg/kg (rabbit)
- LD50 Dermal: 2,000 mg/kg (rabbit)
- LC50 Inhalation: no data

PHENOL (108-95-2):

- LD50 Oral: 340-540 mg/kg (rat)
- LD50 Dermal: 660 mg/kg (rat)
- LC50 Inhalation - 316 mg/l, 4h (rat)

4,4-ISOPROPYLIDENEDIPHENOL, OLIGOMERIC (110839-13-9):

- LD50 Oral: 1,500 mg/kg (rat)
- LD50 Dermal: no data
- LC50 Inhalation: no data

Tetraethylenepentamine (112-57-2):

- LD50 Dermal: 1,260 mg/kg (rabbit)
- LD50 Oral: 1,716.2 mg/kg (rat)
- LD50 Inhalation: No data available

MIXED XYLENES (1330-20-7):

- LD50 Oral: 3,523 mg/kg (rat)
- LD50 Dermal: 1,700 mg/kg (rabbit)
- LC50 Inhalation: 6,700 ppm, 4h (rat)

METAXYLENDIAMINE (1477-55-0):

- LD50 Oral: 980 mg/kg (rat)
- LD50 Dermal: 2,00 mg/kg (rabbit)
- LC50 Inhalation: 1.34 mg/l, 4h (rat)

CRISTALLINE QUARTZ (14808-60-7):

- LD50 Oral: 500 mg/kg (rat)
- LD50 Dermal: 1.0 g/kg (guinea pig)
- LC50 Inhalation: no data

TRIMETHYLHEXAMETHYLENEDIAMINE (25620-58-0):

- LD50 Oral: 910 mg/kg (rat)
- LD50 Dermal: 1,130 md/kg (rabbit)
- LC50 Inhalation: no data

ETHYLENE GLYCOL MONOPROPYL ETHER (2807-30-9):

- LD50 Oral: 3,089 mg/kg (rat)
- LD50 Dermal: 1,337 mg/kg (rabbit)
- LC50 Inhalation: 2,132 ppm, 6h (rat)

ISOPHORONE DIAMINE (2855-13-2):

- LD50 Oral: 1,030 mg/kg (rat)
- LD50 Dermal: no data
- LC50 Inhalation: 4.6 mg/l (rat)

SALICYLIC ACID (69-72-7):

- LD50 Oral: 50 mg/kg (rat)
- LD50 Dermal: > 2,000 mg/kg (rat)
- LC50 Inhalation: 0.9 mg/l, 1h (rat)

CHRONIC TOXICITY

ETHYL BENZENE (100-41-4): Chronic exposure in humans may cause fatigue, sleepiness, headache, and irritation of the eyes and respiratory tract. (HSDB, 2000) Hydrocarbon Solvents - Long-term or repeated exposure of hydrocarbons may lead to hematologic, hepatotoxic, renal, neuropsychiatric, neurological and carcinogenic effects. Hydrocarbons can destroy lipid bilayers and this can lead to "defatting" dermatitis following prolonged skin exposure. Greases, coal pitch, and cutting oils can produce acne and folliculitis. (HSDB, 2004)

PHENOL (108-95-2): Skin is the primary route of entry (for vapor, liquid, and solid forms of phenol). Skin absorption can occur even at low vapor concentration and without significant discomfort. Chronic exposures have been reported to cause death from liver and kidney injuries. It may also affect the pancreas and heart muscle. Other signs and symptoms of chronic exposures include: headache, vertigo, fainting, cough, fatigue, muscle aches and pain, lack of appetite, difficulty swallowing, excess salivation, diarrhea, nausea, vomiting, insomnia, nervousness, weight loss, pallor, partial paralysis, ochronosis, albuminuria, and dark urine. (HSDB, 2003)

MIXED XYLENES (1330-20-7): Exposure to xylene may cause a defatting dermatitis, reversible eye damage, dyspnea, confusion, dizziness, apprehension, memory loss, headache, tremors, weakness, anorexia, nausea, tinnitus, irritability, thirst, liver function test abnormalities, renal impairment, and anemia. Xylene contaminated with benzene has been associated with blood dyscrasias. (HSDB, 2009)

Hydrocarbon Solvents - Long-term or repeated exposure of hydrocarbons may lead to hematologic, hepatotoxic, renal, neuropsychiatric, neurological and carcinogenic effects. Hydrocarbons can destroy lipid bilayers and this can lead to "defatting" dermatitis following prolonged skin exposure. Greases, coal pitch, and cutting oils can produce acne and folliculitis. (HSDB, 2004)

TALC (HYDROUS MAGNESIUM SILICATE): Chronic inhalation of industrial talc dusts or body talc produces talcosis due to talc, silica, and asbestos (talc pneumoconiosis) characterized by productive cough, dyspnea, rales, diminished breath sounds, limited chest expansion, interstitial fibrosis, and granulomas.

CRYSTALLINE QUARTZ (14808-60-7): Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling and sometimes fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. Individuals with silicosis are predisposed to develop mycobacterial infections (tuberculous and non-tuberculous) and fungal infections.

ETHYLENE GLYCOL MONOPROPYL ETHER (2807-30-9): Glycol ethers are used widely in industrial settings and chronic exposure may occur in many workers among certain industries. In chronic inhalation exposures, there have been reports of gynecologic disorders (benign neoplasms, cervical erosions, menstrual disorders), decreased sperm counts, leukopenia, mild anemia or granulocytopenia, and kidney injury (hematuria, albuminuria). (HSDB, 1996)

SALICYLIC ACID (69-72-7): Hepatic injury has been reported with chronic toxicity. (HSDB, 2008)

NOTE: Chronic exposure to organic solvents has been associated with various neurotoxic effects including permanent

brain and nervous system damage. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL TO FATAL.

CARCINOGENICITY

IARC: Yes

NTP: Yes

OSHA: No

ETHYL BENZENE (100-41-4) is classified as a Group 2B cancer agent (possibly carcinogenic to humans) by IARC (Monograph No. 77).

CRYSTALLINE QUARTZ (14808-60-7) is classified as a known carcinogen by NTP (13th Report on Carcinogens) and as a Group 1 cancer agent (carcinogenic to humans) by IARC (Monographs No. 68 & 100C). The ACGIH classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

MUTAGENICITY

PHENOL (108-95-2) is classified as a Group 2 germ cell mutagen by ECHA according to GHS and CLP regulations. It causes concern for humans owing to possible mutagenic effects.

REPRODUCTIVE TOXICITY

SALICYLIC ACID (69-72-7) is listed as a suspected human reproductive or developmental toxicant (Group 2) by ECHA according to GHS and CLP regulations.

SENSITIZATION

Tetraethylenepentamine (112-57-2) is classified as a Group 1 skin sensitizer and a Group 1 respiratory sensitizer by ECHA according to GHS and CLP regulations.

METAXYLENEDIAMINE (1477-55-0) is listed as a Group 1 skin sensitizer by ECHA according to GHS and CLP regulations.

TRIMETHYLHEXAMETHYLENEDIAMINE (25620-58-0) is listed as a Group 1 skin sensitizer by ECHA according to GHS and CLP regulations.

ISOPHORONE DIAMINE (2855-13-2) is classified as a Group 1 skin sensitizer by ECHA according to GHS and CLP regulations.

12. ECOLOGICAL INFORMATION

Ecological testing or classification has not been conducted for this product as a whole. Available ecological data for individual ingredients is summarized below:

ECOTOXICITY

ETHYL BENZENE (100-41-4):

- Rainbow trout: LC50 - 4.2 mg/l (96h, semi-static test)
- Daphnia magna: EC50 - 2.2 mg/l (1d, static)
- Algae: EC50 - 3.6-4.6 mg/l (72h)
- Earthworms: LC50 - 0.047 mg/cm2 (2d)

PHENOL (108-95-2):

- Daphnia magna: EC50 - 3.1 mg/l (48h)
- Fish: LC50 - 8.9 mg/l (96h)

Tetraethylenepentamine (112-57-2)

- Rainbow trout: LC50 - 420 mg/l (96h)
- Daphnia magna: EC50 - 24.1 mg/l (48h)
- Microalgae: EC50 - 6.8 mg/l (72h, growth inhibition)

MIXED XYLENES (1330-20-7):

- Crustaceans: LC50 - 8.5 ppm (48h)
- Rainbow fish: LC50 - 2.6 mg/l (96h, semi-static test)
- Fathead minnow: LC50 - 9.09 mg/l (96h)
- Daphnia magna: EC50 - 75.49 mg/l (24h)
- Algae: EC50 - 4.36 mg/l (73h, static test)

METAXYLENEDIAMINE (1477-55-0):

- Japanese rice fish: LC50 - 87.6 mg/l (96h, semi-static test)
- Daphnia magna: EC50 - 15.2 mg/l (48h, static test)

- Algae: EC50 - 32.1 mg/l (72h, static test)
 - Bacteria: EC50 > 1,000 mg/l (30h, sludge treatment)
- CRYSTALLINE QUARTZ (14808-60-7):
- Fish: EC50 - 100 mg/l
 - Algae: EC50 - 100 mg/l
 - Daphnia magna: EC50 - 100 mg/l
- TRIMETHYLHEXAMETHYLENEDIAMINE (25620-58-0):
- Fish: LC50 - 17.2 mg/l (48h)
 - Daphnia magna: EC50 - 31.5 mg/l
 - Algae: EC50 - 29.5 mg/l (72h)
- ETHYLENE GLYCOL MONOPROPYL ETHER (2807-30-9):
- Fathead minnow: LC50 - 91.3 mg/l
 - Daphnia magna: LC50 - 91.3 mg/l (96h)
- ISOPHORONE DIAMINE (2855-13-2):
- Bacteria: EC50 - 1,120 mg/l (18h)
 - Algae: EC50 - 37 mg/l (72h)
 - Daphnia magna: EC50 - 28 mg/l (48h)
- SALICYLIC ACID (69-72-7):
- Daphnia magna: EC50 - 10-50 mg/l (48h)

PERSISTENCE AND DEGRADABILITY

- ETHYL BENZENE (100-41-4): Readily biodegradable (100% in 6 days).
- PHENOL (108-95-2): Readily biodegradable.
- Tetraethylenepentamine (112-57-2): Not biodegradable (17% in 84 days)

- MIXED XYLENES (1330-20-7): Readily biodegrades in soil and ground water (72%).
- METAXYLENEDIAMINE (1477-55-0): Not readily biodegradable (49% in 28 days).
- CRYSTALLINE QUARTZ (14808-60-7): Not biodegradable.
- TRIMETHYLHEXAMETHYLENEDIAMINE (25620-58-0): Biodegradable.
- ISOPHORONE DIAMINE (2855-13-2): Not readily biodegradable.

BIOACCUMULATIVE POTENTIAL

- ETHYL BENZENE (100-41-4): Low potential to bioaccumulate (log Pow = 3.15 (measured)).
- PHENOL (108-95-2): Low potential to bioaccumulate.
- Tetraethylenepentamine (112-57-2): Low potential to bioaccumulate (Logpow = -3.16)
- MIXED XYLENES (1330-20-7): Bioconcentration potential is low (log Pow = 2.77-3.15).
- ISOPHORONE DIAMINE (2855-13-2): Low potential to bioaccumulate.

MOBILITY IN ENVIRONMENTAL MEDIA (SOIL, WATER)

- ETHYL BENZENE (100-41-4): Potential in soil is low. Partition coefficient (Koc) - 518 (estimated).
- MIXED XYLENES (1330-20-7): Potential in soil is medium: Partition coefficient (Koc) - 443 (estimated).

13. DISPOSAL CONSIDERATIONS

DESCRIPTION OF WASTE RESIDUES

Any surplus materials, by-products, or sludge. Empty containers or liners may retain some product residue.

HANDLING OF WASTE

Wash hands thoroughly with soap and water after use.

Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Vapor from product residues may create a highly flammable atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally.

METHODS OF DISPOSAL

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste mixtures should be tested to determine the applicable EPA hazardous waste number. Also, reference RCRA information in section 15 if listed. Some waste materials are amenable to recycling or reuse. Dispose of in accordance with local, state and federal regulations. Incinerate in approved facility. Do not incinerate closed containers. Waste should not be disposed of via drains or the sewer.

14. TRANSPORT INFORMATION

DOT CLASSIFICATION

UN1263,PAINT,3,II

ENVIRONMENTAL HAZARDS

Marine Pollutant - No

TRANSPORT IN BULK

Not applicable.

SPECIAL PRECAUTIONS

If transported within user's premises:

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

If transported outside of user's premises:

The shipping description provided here is for informational purposes only. The person offering the product for transport is responsible for complying with the applicable regulations. Review all packaging for suitability prior to shipment.

15. REGULATORY INFORMATION

U.S. REGULATIONS

HCS CLASSIFICATION

See section 2.

UNITED STATES INVENTORY (TSCA 8B)

All chemicals in this product are listed, or are exempt from listing, on the TSCA inventory.

SARA 304

PHENOL (108-95-2): RQ 1,000 LB

SARA 313 TOXIC CHEMICALS

ETHYL BENZENE (100-41-4)

PHENOL (108-95-2)

MIXED XYLENES (1330-20-7)

ETHYLENE GLYCOL MONOPROPYL ETHER (2807-30-9) - N230 (Glycol Ether)

SARA 302 EXTREMELY HAZARDOUS SUBSTANCES

PHENOL (108-95-2): TPQ 500/10,000 LB

CERCLA HAZARDOUS SUBSTANCES

ETHYL BENZENE (100-41-4): RQ 1000 LB

PHENOL (108-95-2): RQ 1,000 LB

MIXED XYLENES (1330-20-7): RQ 100 LB

ETHYLENE GLYCOL MONOPROPYL ETHER (2807-30-9) - Glycol Ethers

RCRA HAZARDOUS WASTE

PHENOL (108-95-2): U188

MIXED XYLENES (1330-20-7): U239

CAA Section 112(b) HAZARDOUS AIR POLLUTANTS

ETHYL BENZENE (100-41-4)

PHENOL (108-95-2)

MIXED XYLENES (1330-20-7)

ETHYLENE GLYCOL MONOPROPYL ETHER (2807-30-9) - Glycol Ethers

CAA Section 112(r) SUBSTANCES FOR ACCIDENTAL RELEASE PREVENTION

This product does not contain a chemical which is listed in Section 112(r).

PROPOSITION 65 (CALIFORNIA)

Warning: This product contains a chemical known to the State of California to cause cancer: ETHYL BENZENE (100-41-4).

Warning: This product contains a chemical known to the State of California to cause cancer: CRYSTALLINE QUARTZ

(14808-60-7) when in the form of airborne, unbound particles of respirable size.

16. OTHER INFORMATION

DATE OF REVISION

1/29/2024

PREPARED BY

Rebecca Granados

MANUFACTURER DISCLAIMER

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best of the preparer's knowledge. However, since the use of this information and the conditions of the use of the product are not under the control of the preparer, it is the user's obligation to determine conditions of safe use of the product.